

# JFX200-2531



dual-bed UV-LED flatbed inkjet printer

98.4" x 122"

## Dual-capacity UV-LED flatbed printer

The JFX200-2531 dual-bed printer increases productivity by enabling printing to continue from one origin while the other is being loaded or unloaded. With dual origin points, two or more boards or position jigs can be loaded onto the table for continuous printing – while one board is printing, the next one can be mounted and prepared without stopping production. A standard ionizer bar greatly reduces image quality issues that can be caused by static electricity.

- Maximum print area 98.4" x 122" (2.5 x 3.1 m)
  - > Print on one oversized sheet, or multiple position jigs or smaller substrates
  - > Designed for continuous high volume production
- Layout pins ensure proper media alignment at either origin
- High quality print resolution of up to 1,200 dpi
- Variable Dot Technology and Mimaki Advanced Pass System (MAPS) for smooth solids and gradients
- User selectable dual zones per origin hold media flat
- Mimaki Circulation Technology (MCT) for White ink prevents settling
- Nozzle Recovery System
- Low-energy UV-LED lamps last five years or more
- Table ships in two parts that are joined on-site for easy installation

*For best results, always use Mimaki original inks*

# Mimaki™ JFX200-2531

<b>Printhead</b>	On-demand piezo (2 printheads in a staggered configuration)
<b>Print resolution</b>	300 dpi, 450 dpi, 600 dpi, 900 dpi, 1,200 dpi
<b>Print speed</b>	up to 269 SqFt (25 SqM) / Hr
<b>Maximum print area</b>	98.4 in W x 122 in L (2,500 x 3,100 mm)
<b>Maximum thickness</b>	2.0 in (50 mm)
<b>Maximum media weight</b>	110.2 lb / SqFt (50kg / SqM), non-concentrated
<b>Ink Type/Color</b>	LH-100 UV: For high scratch and chemical resistance – C M, Y, K, W, Clear LUS-150 UV: For balanced adhesion and flexibility – C, M, Y, K, Lc, Lm, W LUS-200 UV: For more flexible outdoor applications – C, M, Y, K, W LUS-350 UV: Up to 350% elongation for thermoforming applications – C, M,Y, K, W PR-100 UV Primer PR-200 UV Primer
<b>Ink Package size</b>	1 liter bottles
<b>Flatbed table</b>	Vacuum system (standard), 4 user-selectable zones Layout pins and Ionizer (standard)
<b>Certifications</b>	VCCI-Class A, FCC-Class A, ETL UL 60950-1 CE Marking (EMC, Low Voltage Directive, Machinery Directive), CB Report, RoHS
<b>Interface</b>	USB 2.0
<b>Power supply</b>	AC 200-240V, 50/60 Hz
<b>Power consumption</b>	Up to 2.88 kVA
<b>Operational environment</b>	Temperature: 59 – 86 °F (15 – 30 °C) Accuracy guaranteed at 64.4 – 77 °F (18 – 25 °C) Humidity: 35 – 65% Rh (Non condensing)
<b>Dimensions (W x D x H)</b>	173.2 x 161.4 x 49.2 in (4,400 x 4,100 x 1,250 mm)
<b>Weight</b>	Approx. 2205 lbs. (1000 kg)

dual-bed UV-LED flatbed inkjet printer

98.4" x 122"



Expertos en impresión digital

## Publicidad

Telefono: +57 1 611 47 64  
E-mail: mercadeo@grafix.com.co

Dirección: Carrera 11A N° 93 A - 62 Oficina: 201  
Bogotá, Colombia.  
www.grafix.com.co



Please visit us at: [www.mimakiusa.com](http://www.mimakiusa.com)

Mimaki USA, Inc.  
150-A Satellite Blvd NE, Suwanee, GA 30024

Print speeds are based on factory tests. Total throughput depends upon front-end driver/RIP, file size, printing resolution, ink coverage, network speed, etc. For best performance, always use Mimaki original inks. Specifications subject to change without notice.

Mimaki is a trademark of Mimaki Engineering Co. Ltd. Copyright 2016, Mimaki USA, Inc.

Rev. 11/10/16